



PC 300 MULTI-PARAMETER MONITOR

TECHNICAL CHARACTERISTICS

DIMENSIONS:

HEIGHT: 165 MM
WIDTH: 96 MM
THICKNESS: 68 MM

BASIC EQUIPMENT:

- ADULT SpO2 TUBE
- ADULT BRACELET
- EAR THERMOMETER
(TUBE COVER NOT INCLUDED)
- LITHIUM BATTERY WITH CHARGER
- TRANSPORT BAG
- USER MANUAL: GB, FR, IT, ES

CERTIFICATIONS:

MEDICAL DEVICE CLASS : II A
NSIS: 1316220
CND: Z1203020202
EAN/UPC: 8023279351620
GMDN: 57960
PARAF: 977815493

PRODUCT CODE:

TEC01777 PC 300 MULTI-PARAMETER
MONITOR



PC-300 portable monitor measures SpO2, the pulse frequency and the temperature. Suited for home and hospital use, it is equipped with Bluetooth technology and USB interface. Also it allows to transfer the data on the PC tablet and smartphone (Android and iOS systems).

It is able to produce up to 6.000 pressure records up to 100 different patients (each user can record 999 measurements) and it contains an ear tube that can measure the temperature in 5 seconds.

Pediatric NIBP and SpO2 pediatric tube are included but are an optional.

ECG and glucometer are an optional

Communication protocols are available on demand.

Rechargeable lithium battery is included in the package:

- BATTERY : 3.7 V LI-ON BATTERY INCLUDED
- EXERCISE TENSION: 3.6 - 4.2 VDC
- OPERATING CURRENT: 800mA
- CHARGER: 100-240 VAC , 50/60 Hz VDC/ US

TECNOLIFE S.r.l. -

Via Cimarosa, 71 - 40033 Casalecchio di Reno (BO)

tel.051/6259059 – fax.051/0510419

info@tecnolifesrl.com - www.tecnolifesrl.com